

# The extract package \*

Hendri Adriaens

v1.9a (2019/09/18)

## Abstract

This package can be used to (conditionally) extract specific commands and environments from a source file and write them to a target file. This can be done without significant changes to the source document, but labels inside the source can be used for more flexibility. The package also provides environments to write code directly to the target file or use code in both the source and the target file. These tools allow one to generate ready-to-run files from a source document, containing only the extracted material, in an otherwise ordinary  $\LaTeX$  run.

## Contents

<b>1 Introduction</b>	<b>1</b>	<b>6 How it works, limitations</b>	<b>10</b>
<b>2 Environment extraction</b>	<b>2</b>	<b>7 Source and examples</b>	<b>11</b>
<b>3 Command extraction</b>	<b>3</b>	<b>8 Implementation</b>	<b>11</b>
<b>4 Conditional extraction</b>	<b>4</b>	<b>References</b>	<b>26</b>
4.1 Extraction with numbers . . .	4	<b>Acknowledgements</b>	<b>27</b>
4.2 Extraction with labels . . . .	5	<b>Version history</b>	<b>27</b>
<b>5 Extraction tools</b>	<b>6</b>	<b>Index</b>	<b>28</b>
5.1 Manual extraction . . . . .	6		
5.2 Skipping extraction . . . . .	8		
5.3 Miscellaneous options . . . .	9		

## 1 Introduction

I created this package when I was working on some lecture notes with exercises in the text and wanted to generate an exercises book on the fly. David Carlisle put forward the idea to use a technique as is now implemented in this package. The package heavily uses the verbatim package [13] by Rainer Schöpf and uses the xkeyval package [1] to provide a simple and easy interface<sup>1</sup>.

There are other packages around that provide tools for conditionally typesetting material or writing material to an external file. Let me list a few.

\*This package can be downloaded from the CTAN mirrors: `/macros/latex/contrib/extract`. See `extract.dtx` for information on installing extract into your  $\LaTeX$  distribution and for the license of this package.

<sup>1</sup>And some tools like `\XKV@ifundefined` and `\XKV@sp@deflist`. See section 8 for more information.

askinclud [12], excludeonly [9]

These packages enhance  $\TeX$ 's `\include` and `\includeonly` system to select the files that should be included in typesetting.

comment [6], verbatim [13], xcomment [14]

The first two packages define the `comment` environment and the third the `xcomment` environment. These environments ignore their body. But if the command `\xcomment` is used and supplied with a list of environments, these environments will be typeset when they appear in the body of the `xcomment` environment. The `comment` package provides the commands `\includecomment` and `\excludecomment` to do a similar job.

optional [3], version [4], versions [8]

These packages define some commands with which you can control which material should be typeset.

pagesel [11], pdfpages [10], selectp [2]

These packages only typeset certain pages.

fancyvrb [15], listings [7]

These packages (among others) provide tools to write text to an external file.

The `extract` package differs from all these packages since it extracts content and leaves the typeset version of the original document untouched. Furthermore, for simple extraction jobs, it is not necessary to make any changes to the document other than adding the `\usepackage` command. This allows for conditional extraction of commands and environments based on the number of the command or environment counted from the beginning of the document. More flexible conditional extraction can be achieved by adding labels to the source document. How all of this works will be explained in the sections to come.

## 2 Environment extraction

The following provides an example of the user interface of the package.

```
\usepackage[
  active,
  generate=file,
  extract-env={figure,table}
]{extract}
```

*options*  
*active*  
*generate*  
*extract-env*

If the `active` option is not specified (or set to `false`), the package does nothing and no files are generated. If the option is specified, the package will redefine the environments `figure` and `table` so that they write their bodies (the content of the environment) to the file indicated with the `generate` option, here `file.tex`<sup>2</sup>, including the `\begin{figure}` and `\end{figure}` commands. Besides that, the environments will be executed as usual. Most environments are supported (known exception is the `document` environment). When the package encounters `\begin{document}` or `\end{document}` in the source file, by default<sup>3</sup>, it will also write these commands to the target file, such that, if a suitable preamble is added, the file is ready to be run by

<sup>2</sup>If a file extension is lacking, `.tex` will be used.

<sup>3</sup>See section 5.3 for the `handles` option.

L<sup>A</sup>T<sub>E</sub>X. See listing 1 for an example.<sup>4</sup> The package will also write a header to the target

xtrex1.tex	file.tex
<pre>\documentclass[10pt]{article} \usepackage[   active,   generate=file,   copydocumentclass=false,   extract-env=equation ]{extract} \begin{extract} \documentclass[11pt]{article} \end{extract} \begin{document} Some text. \begin{equation} a^2+b^2=c^2 \end{equation} Some text. \begin{equation} x^2+y^2=z^2 \end{equation} Some text. \end{document}</pre>	<pre>\documentclass[11pt]{article} \begin{document} \begin{equation} a^2+b^2=c^2 \end{equation} \begin{equation} x^2+y^2=z^2 \end{equation} \end{document}</pre>

Listing 1: Environment extraction.

file with some information about the source and time of generation of the target file. This header can be turned off with the `no-header` option. See also section 5.3.

### 3 Command extraction

*options*  
`extract-cmd`  
`extract-cmdline`

This package can also extract commands. It supplies two methods to do this. See the example below.

```
\usepackage[
  active,
  generate=file,
  extract-cmd=section,
  extract-cmdline=label
]{extract}
```

The first method (accessed with the `extract-cmd` option) is based on the particular syntax of the command and hence only supports particular commands. It will read its arguments and write them, together with the original command, to the target file. Besides that, the command will be executed as usual. Currently, the commands `\chapter`, `\section`, `\subsection`, and `\subsubsection` in the standard L<sup>A</sup>T<sub>E</sub>X classes (and classes or packages derived from those) are supported. An optional argument to these commands, like `\chapter[short]{long}` is supported. However, the starred version `\chapter*{title}` will not be written to the file due to technical limitations. Sections 6 and 8 will explain this in more detail.

The second method (accessed with the `extract-cmdline` option) will redefine commands to write themselves and all the text following on the same line to the target

<sup>4</sup>See section 5.1 for the `extract` environment, section 5.3 for the `copydocumentclass` option and section 7 how to obtain the example files.

file and will also execute the entire line as with an ordinary  $\text{\LaTeX}$  run. This allows to re-define any command that is not supported by the first method, but should be applied with care. If the command is used internally in a class or style file, your document might fail to run. In particular, one should not redefine one of the commands supported by the first method with this method. See listing 2 for a working example of both methods.<sup>5</sup>

xtrex2.tex	file.tex
<pre> \documentclass{article} \usepackage[   active,   generate=file,   extract-env=exercise,   extract-cmd=section,   extract-cmdline=label ]{extract} \begin{extract*} \newtheorem{exercise}{Exercise} \end{extract*} \begin{document} \section{Theory} \label{sec:1} Some text. \section{Exercises} \begin{exercise} Use the results from section \ref{sec:1} to show that\dots \end{exercise} Some text. \end{document} </pre>	<pre> \documentclass{article} \newtheorem{exercise}{Exercise} \begin{document} \section{Theory} \label{sec:1} \section{Exercises} \begin{exercise} Use the results from section \ref{sec:1} to show that\dots \end{exercise} \end{document} </pre>

Listing 2: Command extraction.

## 4 Conditional extraction

### 4.1 Extraction with numbers

*options* It is also possible to conditionally extract environments and commands. After the op-  
*-nrs* tions `extract-env`, `extract-cmd` and `extract-cmdline` are used, for each environment or command specified there, there will be a new option with the name of that environment or command and the `-nrs` postfix. This option can take a comma separated list in which you can specify which environments or macros (counting from the `\usepackage{extract}` command<sup>6</sup>) should be extracted. Table 1 on page 5 lists the syntax that can be used in the comma separated list. The term ‘item’ is used for ‘command or environment’. See an example in the listing below.

```

\documentclass{book}
\usepackage[
  active,
  generate=file,

```

<sup>5</sup>See section 5.1 for the `extract*` environment.

<sup>6</sup>Notice that starred commands like `\chapter*`, which won't be redefined by the `extract-cmd` option, will also not be counted.

Syntax	Meaning
$\langle x \rangle$	Item $\langle x \rangle$ will be extracted.
$-\langle x \rangle$	All items up to and including item $\langle x \rangle$ will be extracted.
$\langle x \rangle-$	All items from and including item $\langle x \rangle$ will be extracted.
$\langle x \rangle-\langle y \rangle$	All items in between $\langle x \rangle$ and $\langle y \rangle$ , including $\langle x \rangle$ and $\langle y \rangle$ will be extracted.

Table 1: Syntax for conditional extraction with numbers.

```
extract-env={figure,table},
figure-nrs={-2,4-},
extract-cmd=chapter,
chapter-nrs={3-5,7}
]{extract}
\begin{document}
...
\end{document}
```

This example, when completed with content, will extract all `table` environments, figure environments 1, 2, and all figures from (and including) figure 4. It will also extract chapter commands 3 to 5 and 7.

## 4.2 Extraction with labels

*options* Conditional extraction is also possible with labels. The advantage of using labels is that  
*-labels* output does not change (in comparison to using numbers) when commands or environments are added. The drawback is that one needs to modify the source document and add labels in the text.

`\extractionlabel` Labels are declared with the following command.

```
\extractionlabel{\name}
```

A label should be declared just before the command or environment that you want to extract. For instance

```
\extractionlabel{exer-a}
\begin{exercise}
...
\end{exercise}
```

You can reuse the same label multiple times and you can specify which items should be extracted by the options with a `-labels` prefix. This works in the same way as with numbers.

```
\documentclass{book}
\usepackage[
active,
generate=file,
extract-env=exercise,
exercise-labels={exer-a,exer-c}
]{extract}
\begin{document}
...
\end{document}
```

This example will only extract exercises that have been preceded by the declaration `\extractionlabel{exer-a}` or `\extractionlabel{exer-c}`.

When using both conditional extraction with numbers and with labels, the command or environment at hand will be extracted when at least one of the conditions is true. Find an example in listing 3.

xtrex3.tex	file.tex
<pre> \documentclass{article} \usepackage[   active,   generate=file,   extract-env=figure,   figure-nrs={1,3},   figure-labels={fig-a,fig-b} ]{extract} \begin{document} Some text. \begin{figure} Figure 1. \end{figure} Some text. \extractionlabel{fig-a} \begin{figure} Figure 2. \end{figure} Some text. \extractionlabel{fig-b} \begin{figure} Figure 3. \end{figure} Some text. \extractionlabel{fig-c} \begin{figure} Figure 4. \end{figure} \end{document} </pre>	<pre> \documentclass{article} \begin{document} \begin{figure} Figure 1. \end{figure} \begin{figure} Figure 2. \end{figure} \begin{figure} Figure 3. \end{figure} \end{document} </pre>

Listing 3: Conditional extraction.

## 5 Extraction tools

### 5.1 Manual extraction

*environment* `extract` The package provides the environment `extract`.

```

\begin{extract}
<body>
\end{extract}

```

This environment writes its body only to the target file. This can be used to generate a preamble in the target file so that you can run the generated file through  $\TeX$  immediately after creation. See the example in listing 1 on page 3 and the example below.

*environment* `extract*` There also exists a starred version of the `extract` environment.

```

\begin{extract*}

```

```

<body>
\end{extract*}

```

This environment will not only write the body to the target file, but will also execute the code in the source document. This can be used to create a common preamble which holds packages and commands that will be used in both the source and the target file. See listing 2 on page 4 and listing 4 for examples. Notice that the ‘answer’ will not appear in xtrex4.dvi.

xtrex4.tex	file.tex
<pre> \documentclass{article} \usepackage[   active,   generate=file,   extract-env=equation* ]{extract} \begin{extract*} \usepackage{amsmath} \end{extract*} \begin{document} Some text. \begin{equation*} x^2+y^2=z^2 \end{equation*} \begin{extract} \$x=3\$, \$y=4\$ and \$z=5\$ satisfy this equation. \end{extract} \end{document} </pre>	<pre> \documentclass{article} \usepackage{amsmath} \begin{document}  \begin{equation*} x^2+y^2=z^2 \end{equation*} \$x=3\$, \$y=4\$ and \$z=5\$ satisfy this equation.  \end{document} </pre>

Listing 4: Extract environments.

```

\extractline
\extractline*

```

The package also provides a command that extracts the current line.

```

\extractline
\extractline*

```

The starred version also executes the code at that line. See the example below.

```

\extractline This line should be extracted.
\extractline*This line should be extracted and executed.

```

Notice that a space is following the command `\extractline` and that no space is following the command `\extractline*`. In the first line,  $\TeX$  will eat this space, but it won't do that in the second line. If we add a space there in between the `*` and `This`, this space will be executed and extracted as well.

```

\extractline
\extractline*
environments

```

```

extract
extract*

```

```

\begin{extract}[\langle name \rangle]
\begin{extract*}[\langle name \rangle]
\extractline[\langle name \rangle]
\extractline*[\langle name \rangle]

```

*options*  
 extract-nrs  
 line-nrs  
 extract-labels  
 line-labels

The options `extract-nrs` and `line-nrs` can be used to control conditional extraction of these environments and commands using numbers. Moreover, one can do conditional extractions with labels for these commands and environments as well. Use the options `extract-labels` and `line-labels` for that purpose. See also section 4 for information about conditional extraction.

See an example in listing 5. This example will demonstrate that only certain lines and environments are extracted. Note that, when running `xtrex5.tex` with  $\LaTeX$ , the output, `xtrex5.dvi`, will contain the following.

```
line 2
line 4
line 5
```

xtrex5.tex

file.tex

```
\documentclass{article}
\usepackage[
  active,
  generate=file,
  copydocumentclass=false,
  extract-labels=type-a,
  line-labels={type-a,type-c},
  line-nrs=3
]{extract}
\begin{extract}[type-a]
\documentclass{article}
\end{extract}
\begin{extract}[type-b]
\documentclass{book}
\end{extract}
\begin{document}
\parindent0pt
\extractline[type-a]line 1\\
\extractline*line 2\\
\extractline line 3\\
\extractline*[type-a]line 4\\
\extractline*[type-c]line 5\\
\extractline line 6\\
\end{document}
```

```
\documentclass{article}
\begin{document}
line 1\\
line 3\\
line 4\\
line 5\\
\end{document}
```

Listing 5: Optional labels.

## 5.2 Skipping extraction

*environment*  
 extractskip

The package also provides the `extractskip` environment.

```
\begin{extractskip}[\langle name \rangle]
\langle body \rangle
\end{extractskip}
```

The body of this environment will not be written to the target file, but will be executed. This environment can be used to skip material in an environment which extracts its entire body. This could be the `extract` environment, but also an environment that has been redefined to be extracted using the `extract-env` option. The argument  $\langle name \rangle$  is optional and contains the label.



*options*  
 extractskip-nrs  
 extractskip-labels

This environment can also operate conditionally as has been described in section 4 using the options `extractskip-nrs` and `extractskip-labels`. Listings 6 and 7 on page 10 will demonstrate this environment.

<p>xtrex6.tex</p> <pre style="border: 1px solid black; padding: 5px;"> \documentclass{article} \usepackage[   active,   generate=file,   extract-env=figure ]{extract} \begin{document} \begin{figure}[!h] \begin{extractskip} \fbbox{figure 1} \end{extractskip} \fbbox{figure 2} \end{figure} \begin{extract*} \begin{itemize} \item 1 \item 2 a\begin{extractskip}b \item 3 c\end{extractskip}d \item 4 \begin{extractskip} \item 5 \end{extractskip} \end{itemize} \end{extract*} \end{document} </pre>	<p>file.tex</p> <pre style="border: 1px solid black; padding: 5px;"> \documentclass{article} \begin{document} \begin{figure}[!h] \fbbox{figure 2} \end{figure} \begin{itemize} \item 1 \item 2 a d \item 4 \end{itemize} \end{document} </pre>
---	--

Listing 6: Skipping extraction.

### 5.3 Miscellaneous options

- option* `header` When setting the header option to `false`, no header will be written to the target file. If the option is not specified or set to `true`, the package will write a header to the target file including information on when the target file was generated and which source file was used.
- option* `handles` This option controls whether the package will write `\begin{document}` and `\end{document}` to the target file when it encounters these commands in the source document. By default, this option is set to `true`. When the option is set to `false`, the generated file can be `\inputed` or `\included` by another file immediately after production.
- option* `copydocumentclass` This option control whether the target file should get the same `\documentclass` command as the source document (including class options). If set to `false`, you should specify another document class for the target file, for instance using the `extract` environment. See listing 1 on page 3 for an example.

xtrex7.tex

file.tex

```

\documentclass{article}
\usepackage[
  active,
  generate=file,
  extractskip-labels=skipb
]{extract}
\begin{document}
\begin{extract*}
\begin{itemize}
\begin{extractskip}[skipa]
\item 1
\end{extractskip}
\begin{extractskip}[skipb]
\item 2
\end{extractskip}
\begin{extractskip}[skipc]
\item 3
\end{extractskip}
\end{itemize}
\end{extract*}
\end{document}

```

```

\documentclass{article}

\begin{document}
\begin{itemize}
\item 1
\item 3
\end{itemize}

\end{document}

```

Listing 7: Skipping extraction conditionally.

## 6 How it works, limitations

The package works as follows. When an environment is asked to be extracted, the package will first make a backup of the environment with the XTR prefix, for instance, XTR`equation*`. After that, the package will redefine the environment to read the lines of its body verbatim (without executing), parse the lines to locate `extractskip` environments and write all lines to a temporary file and the lines that are not in an `extractskip` environment to a temporary file. After the environment is finished, the temporary file, containing for instance

```

\begin{XTRequation*}
x^2+y^2=z^2
\end{XTRequation*}

```

will be inserted in the source document using `\input`. This works, at least in theory, with most environments. Notice that this method does require a change to the `\begin` and `\end` macros provided by the  $\TeX$  kernel [5]. I had to add a hook to these commands to be able to collect code to be executed after the current environment is ended. In particular, this package will use those hooks to `\input` the original code after finishing the current group. See section 8 for more details.

Commands require a different approach. As a command can have a very specific argument structure, redefining commands safely, without distorting its original behavior, is not possible in general. I have chosen to support the most basic document structure commands as provided by standard  $\TeX$  classes, like `book` and `article`. Extraction of commands from other classes, like provided by the `koma-script` bundle, might work, but there is no guarantee.

To be more precise: when requested, the macros `\@chapter` and `\@sect` will be redefined. These commands are at the basis of all chapter and section commands. When `extract` redefines one of these commands, it first makes a backup, like `\XTR@chapter`.

After that, it will redefine the original command to read its argument(s), export them to the target file and execute the backup with the proper arguments.

An alternative to this, rather restricted method is the method accessed by the `extract-cmdline` option which redefines the commands listed there to read the entire line of text, write that to the target file and afterwards execute it with a backup copy of the original command. This method too has its drawbacks though as you can't redefine commands that are used internally in other macros.

More details on the package code can be found in section 8.

## 7 Source and examples

To generate this documentation, find the source of this package, `extract.dtx` in your local  $\text{\TeX}$  installation or on CTAN and perform the following steps.

```
latex extract.dtx
latex extract.dtx
bibtex extract
makeindex -s gglo.ist -o extract.gls extract.glo
makeindex -s gind.ist -o extract.ind extract.idx
latex extract.dtx
latex extract.dtx
```

If you only want to produce the package and example files from the source, then the first step is sufficient. This step will generate the package file `extract.sty` and the example files `xtrex1.tex`, `xtrex2.tex`, `xtrex3.tex`, `xtrex4.tex`, `xtrex5.tex`, `xtrex6.tex` and `xtrex7.tex`.

## 8 Implementation

Initializations.

```
1%<*extract>
2\NeedsTeXFormat{LaTeX2e}[1995/12/01]
3\ProvidesPackage{extract}
4 [2019/09/18 v1.9a extract content from document (HA)]
5\RequirePackage{verbatim}
6\RequirePackage{xkeyval}
7\newwrite\XTR@out
8\newwrite\XTR@tmp
9\newif\ifXTR@st
10\newif\ifXTR@skip
11\newif\ifXTR@extract

\XTR@err {<text>}
Error macro.
12\def\XTR@err#1{\PackageError{extract}{#1}\@ehc}

\XTR@namelet {<cmd1>}{<cmd2>}
Version of \let for two command sequence names.
13\def\XTR@namelet#1#2{%
14 \expandafter\let\csname#1\expandafter\endcsname\csname#2\endcsname
15}
```

*option* Options section, powered by xkeyval. Control extraction with one switch.

*active* 16 \define@boolkey [XTR]{extract.sty} [XTR@]{active} [true] {}

*option* Do not create a header in the target file.

*header* 17 \define@boolkey [XTR]{extract.sty} [XTR@]{header} [true] {}

*option* Extract \begin{document} and \end{document} or not.

*handles* 18 \define@boolkey [XTR]{extract.sty} [XTR@]{handles} [true] {}

*option* Copy the \documentclass command to the target file.

*copydocumentclass* 19 \define@boolkey [XTR]{extract.sty} [XTR@]{copydocumentclass} [true] {}

*option* Entry point for the target file name.

*generate* 20 \DeclareOptionX [XTR]{generate}{\lowercase{\def\XTR@file{#1}}}

*option* Environments that should be extracted.

*extract-env* 21 \DeclareOptionX [XTR]{extract-env}{%  
22 \def\XTR@envs{#1}%  
23 \XKV@for@n{#1}\XTR@tempa\XTR@tempb  
24 }

*option* Commands that should be extracted with the ‘arguments method’.

*extract-cmd* 25 \DeclareOptionX [XTR]{extract-cmd}{%  
26 \def\XTR@cmdsargs{#1}%  
27 \XKV@for@n{#1}\XTR@tempa\XTR@tempb  
28 }

*option* Commands that should be extracted with the ‘line method’.

*extract-cmdline* 29 \DeclareOptionX [XTR]{extract-cmdline}{%  
30 \def\XTR@cmdsline{#1}%  
31 \XKV@for@n{#1}\XTR@tempa\XTR@tempb  
32 }  
33 \def\XTR@tempb{%

*options* For each environment or command provide new package options that save the argument to a list cleared from redundant spaces. The -nrs options also create a ‘counter’ for counting the commands or environments. The lists and counters will be used for conditional extraction. Note that \XTR@tkey contains the key name inside the option macro (due to the use of \ProcessOptionsXi).

*-nrs* 34 \DeclareOptionX [XTR]{\XTR@tempa-nrs}{%  
35 \expandafter\XKV@sp@deflist\csname XTR@\XKV@tkey\endcsname{##1}%  
36 \XTR@namelet{XTR@\XKV@tkey @cnt}{z@}%  
37 }%  
38 \DeclareOptionX [XTR]{\XTR@tempa-labels}{%  
39 \expandafter\XKV@sp@deflist\csname XTR@\XKV@tkey\endcsname{##1}%  
40 }%  
41 }

*options* Generate options for \extractline commands.

*line-nrs* 42 \def\XTR@tempa{line}\XTR@tempb

*line-labels* Generate options for extract environments.

*options* 43 \def\XTR@tempa{extract}\XTR@tempb

*extract-nrs* Generate options for extractskip environments.

*extract-labels* 44 \def\XTR@tempa{extractskip}\XTR@tempb

*options* Generate an error for unknown options.

*extractskip-nrs* 45 \DeclareOptionX\*{\XTR@err{Unknown option ‘\CurrentOption’}}

*extractskip-labels*

Initialize options.

```
46\ExecuteOptionsX[XTR]{header=true,handles=true,copydocumentclass=true}
```

Process options.

```
47\ProcessOptionsX[XTR]
```

`\XTR@opentmp` Shortcut macros for much used command sequences.

```
\XTR@writetmp 48\def\XTR@opentmp{\immediate\openout\XTR@tmp\jobname.xtr\relax}
```

```
\XTR@closetmp 49\def\XTR@writetmp{\immediate\write\XTR@tmp}
```

```
\XTR@writeout 50\def\XTR@closetmp{\immediate\closeout\XTR@tmp}
```

```
51\def\XTR@writeout{\immediate\write\XTR@out}
```

Perform some checks on the input. Notice the use of `\XKV@ifundefined` which is equal to `\@ifundefined` if no  $\epsilon$ -TeX engine is available and which uses `\ifcename` when it is. In the latter case, testing whether commands are defined does not create an entry in TeX's hash table.

```
52\ifXTR@active
```

```
53 \XKV@ifundefined{XTR@file}{
```

```
54 \XTR@activefalse
```

```
55 \XTR@err{no file to generate; extract deactivated}
```

```
56 }{}
```

```
57 \XTR@opentmp
```

```
58 \XTR@writetmp{%
```

```
59 \string\lowercase{\string\def\string\XTR@tempa{\jobname}}%
```

```
60 }
```

```
61 \XTR@closetmp
```

```
62 \input{\jobname.xtr}
```

```
63 \ifx\XTR@tempa\XTR@file
```

```
64 \XTR@activefalse
```

```
65 \XTR@err{attempt to overwrite source file; extract deactivated}
```

```
66 \fi
```

```
67\fi
```

`\@envdepth` Counter for depth of environments.

```
68\newcount\@envdepth\@envdepth\z@
```

`\begin` `{<environment>}`

Modify the macro `\begin` to allow adding code to a level specific hook which can be executed after `\endgroup` in `\end`. See for more info on this macro the L<sup>A</sup>T<sub>E</sub>X source [5]. We first do this for the new L<sup>A</sup>T<sub>E</sub>X format, which defines robust versions of `\begin` and `\end`.

```
69\@ifl@t@r\fmtversion{2019/10/01}{%
```

```
70{%, new format
```

```
71 \@namedef{begin }#1{%
```

```
72 \@ifundefined{#1}{%
```

```
73 {\def\reserved@a{\@latex@error{Environment #1 undefined}\@eha}}%
```

```
74 {\def\reserved@a{\def\@currenvir{#1}}%
```

```
75 \edef\@currencline{\on@line}}%
```

```
76 \csname #1\endcsname}}%
```

```
77 \@ignorefalse
```

```
78 \begingroup\@endpfalse
```

Advance depth level.

```
79 \global\advance\@envdepth\@ne
```

Initialize the hook for this level.

```
80 \global\@namedef{@afterrendenvhook@\romannumeral\@envdepth}{}%  
81 \reserved@a  
82 }%
```

`\end` `{<environment>}`

Modify `\end` to execute the code collected in the hook.

```
83 \@namedef{end }#1{%  
84 \csname end#1\endcsname\@checkend{#1}%  
85 \expandafter\endgroup\if@endpe\@doendpe\fi
```

Copy current hook code to a temporary macro.

```
86 \expandafter\let\expandafter\reserved@a  
87 \csname @afterrendenvhook@\romannumeral\@envdepth\endcsname
```

Decrease the depth.

```
88 \global\advance\@envdepth\m@ne
```

Execute the hook of the current environment. This is done after decreasing the depth as to avoid level mixing problems when the hook contains another environment. This environment has to be executed at the same level as the environment in which the hook was defined since it is executed after the group and does not belong anymore to the environment in which the hook was defined.

```
89 \reserved@a\relax  
90 \if@ignore\@ignorefalse\ignorespaces\fi  
91 }%
```

`\begin` `{<environment>}`

This is the code for the old format of  $\LaTeX$ .

```
92}{% old format  
93 \def\begin#1{%  
94 \@ifundefined{#1}%  
95 {\def\reserved@a{\@latex@error{Environment #1 undefined}\@eha}}%  
96 {\def\reserved@a{\def\@currentenv{#1}%  
97 \edef\@currentvline{\on@line}%  
98 \csname #1\endcsname}}%  
99 \@ignorefalse  
100 \begingroup\@endpefalse  
101 \global\advance\@envdepth\@ne  
102 \global\@namedef{@afterrendenvhook@\romannumeral\@envdepth}{}%  
103 \reserved@a  
104 }%
```

`\end` `{<environment>}` This is the code for the old format of  $\LaTeX$ .

```
105 \def\end#1{%  
106 \csname end#1\endcsname\@checkend{#1}%  
107 \expandafter\endgroup\if@endpe\@doendpe\fi  
108 \expandafter\let\expandafter\reserved@a  
109 \csname @afterrendenvhook@\romannumeral\@envdepth\endcsname  
110 \global\advance\@envdepth\m@ne  
111 \reserved@a\relax  
112 \if@ignore\@ignorefalse\ignorespaces\fi  
113 }%  
114 }
```

`\AfterEndEnv` Adds code to the macros `\@afterendenvhook@i`, `i`, etc. which will be executed after the group of the current environment.

```
115 \def\AfterEndEnv{%
116   \expandafter\g@addto@macro
117   \csname @afterendenvhook@\romannumeral\@envdepth\endcsname
118 }
```

`\XTR@checkxtr` `{<type>}{<item>}`

Checks whether a certain environment or command should be extracted or skipped. `<type>` is the type of check: for extraction or for skipping content. `<item>` is the name of a command or an environment.

```
119 \def\XTR@checkxtr#1#2{%
120   \@nameuse{XTR@#1false}%
121   \XTR@namelet{XTR@make>true}{XTR@#1true}%
```

First check whether, for this macro or environment, some method of conditional extraction is used. If not, just extract.

```
122   \XKV@ifundefined{XTR@#2-nrs}{%
123     \XKV@ifundefined{XTR@#2-labels}\XTR@make>true}%
124   }{%
```

Advance the ‘counter’.

```
125   \begin@group
126     \expandafter\count@\csname XTR@#2-nrs@cnt\endcsname
127     \advance\count@\@ne
128     \edef\XTR@resa{\expandafter\noexpand\expandafter\gdef\expandafter
129       \noexpand\csname XTR@#2-nrs@cnt\endcsname{\the\count@}}%
130     \expandafter\endgroup\XTR@resa
131   }%
132   \@nameuse{ifXTR@#1}\else
133     \XKV@ifundefined{XTR@#2-labels}{}%
```

If the current label is in the list for extraction, extract it.

```
134     \ifx\XTR@currentlabel\relax\else
135       \expandtwoargs\in@{,\XTR@currentlabel,}%
136       {\,\csname XTR@#2-labels\endcsname,}%
137       \ifin@\XTR@make>true\fi
138     \fi
139   }%
140   \fi
141   \@nameuse{ifXTR@#1}\else
142     \XKV@ifundefined{XTR@#2-nrs}{}%
```

If the current command or environment number is in the list, extract it.

```
143     \expandafter\XTR@ch@ckxtr\csname XTR@#2-nrs\expandafter
144       \endcsname\csname XTR@#2-nrs@cnt\endcsname
145   }%
146   \fi
```

Redefine `\XTR@currentlabel` to avoid extracting all following environments of this type.

```
147   \global\let\XTR@currentlabel\relax
148 }
```

`\XTR@ch@ckxtr`  $\langle list \rangle \langle counter \rangle$   
 Parse the  $\langle list \rangle$  of numbers and compare each item with the  $\langle counter \rangle$  holding the number of the current item.

```

149 \def\XTR@ch@ckxtr#1#2{%
150   \XKV@for@o#1\XTR@resa{\expandafter\XTR@ch@ck@tr\XTR@resa--\@nil#2}%
151 }

```

`\XTR@ch@ck@tr`  $\langle x \rangle - \langle y \rangle - \langle z \rangle \backslash @nil \langle counter \rangle$   
 Parse an element of the list. Basically, decide whether we have x, x-y, x- or -y and act accordingly.

```

152 \def\XTR@ch@ck@tr#1-#2-#3\@nil#4{%
153   \ifx\@empty#1\@empty
154     \ifnum#4>#2 \else\XTR@maketrue\fi
155   \else
156     \ifx\@empty#2\@empty
157       \ifx\@empty#3\@empty
158         \ifnum#4=#1 \XTR@maketrue\fi
159       \else
160         \ifnum#4<#1 \else\XTR@maketrue\fi
161       \fi
162     \else
163       \ifnum#4<#1 \else\ifnum#4>#2 \else\XTR@maketrue\fi\fi
164     \fi
165   \fi
166 }

```

`\extractionlabel` `\XTR@currentlabel` `\extractionlabel` saves its argument (after removing redundant spaces). This label will be used for conditional extraction. `\XTR@currentlabel` is initialized.

```

167 \def\extractionlabel{\KV@sp@def\XTR@currentlabel}
168 \let\XTR@currentlabel\relax

```

`\extract` `\extract*` Define environments that write verbatim to the target file. The starred version also executes the code by writing it to a temp file and inputting it `\AfterEndEnv`, just as with redefining existing environments. When the package is inactive, `extract` is equivalent to the `comment` environment and `extract*` takes its body out of the group and executes it hence acting as if `\begin{extract*}` and `\end{extract*}` were never typed.

```

169 \def\extract{\XTR@stfalse\XTR@extract}
170 \@namedef{extract*}{\XTR@sttrue\XTR@extract}

```

`\XTR@extract` Prepare verbatim reading and check for an optional argument.

```

171 \def\XTR@extract{%
172   \@bsphack
173   \let\do@makeother\dospecials\catcode'\^M\active
174   \@testopt\XTR@@extract\@nil
175 }

```

`\XTR@@extract` [ $\langle label \rangle$ ]  
 Process the optional label, define line processing and start reading verbatim. Do not extract when the package is not active. Use a temporary file to extract the body to in case this needs to be executed in the source document (`extract*` environment).

```

176 \def\XTR@@extract[#1]{%

```



Check state.

```
177 \ifXTR@active
178 \def\XTR@tempa{#1}%
179 \ifx\XTR@tempa\@nnil\else
180 \KV@sp@def\XTR@currentlabel{#1}%
181 \fi
182 \XTR@checkxtr{extract}{extract}%
183 \else
184 \XTR@extractfalse
185 \fi
186 \ifXTR@st\XTR@opentmp\fi
187 \let\verbatim@processline\XTR@processline@begin
188 \verbatim@start
189 }

190 \begingroup
191 \lccode'!='\ \lccode'\'(=\{ \lccode'\)=\'
192 \lowercase{\endgroup
```

`\XTR@processline@begin` This macro starts the reparsing of a line read by verbatim. It is possible to have `\begin{extractskip}` and `\end{extractskip}` on the same line.

```
193 \def\XTR@processline@begin{%
Initialize \@temptokena (used for temp file) and \verbatim@line (used for output
file). Save the original content of \verbatim@line for later use.
194 \@temptokena{ }%
195 \edef\XTR@orig@line{\the\verbatim@line}%
196 \verbatim@line{ }%
197 \expandafter\XTR@testbegin\XTR@orig@line!begin(extractskip)\@nil
198 }
```

`\XTR@testbegin` `<text1>\begin{extractskip}<text2>\@nil`

Checks whether `\begin{extractskip}` occurs.

```
199 \def\XTR@testbegin#1!begin(extractskip)#2\@nil{%
200 \@temptokena\expandafter{\the\@temptokena#1}%
201 \verbatim@line\expandafter{\the\verbatim@line#1}%
202 \def\XTR@tempa{#2}%
```

If `<text2>` empty, there is no `\begin{extractskip}`. Just write the content to file.

```
203 \ifx\XTR@tempa\@empty\XTR@processline@write\else\XKV@afterfi
```

Check the label.

```
204 \XTR@skiplabel#2[]\@nil
```

Should we skip the `extractskip` environment or not?

```
205 \XTR@checkxtr{skip}{extractskip}%
```

Switch to scanning for `\end{extractskip}` in the next line.

```
206 \let\verbatim@processline\XTR@processline@end
```

Remove some stuff that we added and continue scanning for `\end{extractskip}` on the current line.

```
207 \ifx\XTR@tempa\@nnil\XKV@afterelsefi
208 \XTR@testbegin#2\@nil
209 \else\XKV@afterfi
210 \expandafter\XTR@testbegin\XTR@tempa\@nil
```

```

211   \fi
212   \fi
213 }

\XTR@skiplabel <text1>[<label>]<text2>\@nil
This macro checks whether a label is present and sets \XTR@currentlabel if neces-
sary.
214 \def\XTR@skiplabel#1[#2]#3\@nil{%
215   \def\XTR@tempa{#1}%
216   \def\XTR@tempb{#2}%
217   \ifx\XTR@tempa\@empty
218     \ifx\XTR@tempb\@empty
219       \let\XTR@tempa\@nnil
220     \else
221       \KV@sp@def\XTR@currentlabel{#2}%
222       \XTR@sk@plabel#3\@nil
223     \fi
224   \else
225     \let\XTR@tempa\@nnil
226   \fi
227 }

\XTR@sk@plabel <text> [] \@nil
Remove extra brackets from input.
228 \def\XTR@sk@plabel#1[]\@nil{\def\XTR@tempa{#1}}

\XTR@t@stbegin <text>\begin{extractskip}\@nil
Remove the extra \begin{extractskip} and start scanning for \end{extractskip}
in the current line.
229 \def\XTR@t@stbegin#1!begin(extractskip)\@nil{%
230   \XTR@testend#1!end(extractskip)\@nil
231 }

\XTR@processline@end Starts scanning for \end{extractskip} in case this was not on one line together with
\begin{extractskip}. Comparable to \XTR@processline@begin.
232 \def\XTR@processline@end{%
233   \@temptokena{}%
234   \edef\XTR@orig@line{\the\verbatim@line}%
235   \verbatim@line{}%
236   \expandafter\XTR@testend\XTR@orig@line!end(extractskip)\@nil
237 }

\XTR@testend <text1>\end{extractskip}<text2>\@nil
Check whether \end{extractskip} occurs in the line.
238 \def\XTR@testend#1!end(extractskip)#2\@nil{%
239   \@temptokena\expandafter{\the\@temptokena#1}%
Skip material conditionally on labels or numbers.
240   \ifXTR@skip\else\verbatim@line\expandafter{\the\verbatim@line#1}\fi
241   \def\XTR@tempa{#2}%
242   \ifx\XTR@tempa\@empty\XTR@processline@write\else\XKV@afterfi
Switch to scanning for \begin{extractskip} in the next line.
243   \let\verbatim@processline\XTR@processline@begin

```

Continue scanning for `\begin{extractskip}` in the current line.

```
244 \XTR@t@stend#2\@nil
245 \fi
246 }
```

`\XTR@t@stend` *<text>*`\end{extractskip}\@nil`

Remove the redundant `\end{extractskip}` and continue scanning for for the string `\begin{extractskip}` in this line.

```
247 \def\XTR@t@stend#1!end(extractskip)\@nil{%
248 \XTR@testbegin#1!begin(extractskip)\@nil
249 }}
```

`\XTR@processline@write`

Writes the material to the appropriate file. If one of the tokens has become empty, it might be because the line was empty originally or because the parsing and removal of `\begin{extractskip}` and `\end{extractskip}` made it empty. In the latter case, do not write the empty line. In the former case, do write it.

```
250 \def\XTR@processline@write{%
251 \ifXTR@st\ifcat$\the\@temptokena$\else
252 \XTR@writetmp{\the\@temptokena}%
253 \fi\fi
254 \ifXTR@extract\ifcat$\the\verbatim@line$\else
255 \XTR@writeout{\the\verbatim@line}%
256 \fi\fi
257 \ifx\XTR@orig@line\@empty\XTR@writetmp{}\XTR@writeout{}\fi
258 }
```

`\endextract` Stop reading verbatim and if necessary execute the body of the environment after the `extract*` environment.

`\endextract*`

```
259 \def\endextract{\XTR@stfalse\XTR@endextract}
260 \@namedef{endextract*}{\XTR@sttrue\XTR@endextract}
261 \def\XTR@endextract{%
262 \@esphack
263 \ifXTR@st
264 \XTR@closetmp
265 \AfterEndEnv{\input{\jobname.xtr}}%
266 \fi
267 }
```

`\extractskip` The `extractskip` environment when it is not used inside an environment that is redefined to be extracted. Hence this environment makes itself disappear, just as `extract*`, but doesn't write to the output file. The trick with `XTR@activefalse` will remain local.

`\endextractskip`

```
268 \@namedef{extractskip}{\XTR@activefalse\@nameuse{extract*}}
269 \XTR@namelet{endextractskip}{endextract*}
```

`\extractline` This macro extracts all text after the macro and at the same line. First we check for an optional star.

```
270 \def\extractline{%
271 \XKV@ifstar{\XTR@sttrue\XTR@extractline}%
272 {\XTR@stfalse\XTR@extractline}%
273 }
```

`\XTR@extractline` Start the group and reset all catcodes for verbatim reading.

```
274 \def\XTR@extractline{%
275   \begingroup
276   \let\do\@makeother\dospecials\catcode'\^M\active
```

Test for an optional argument. Note that, due to reset catcodes, macros won't work in the optional argument, but that is not a real restriction, while it saves some tokens and memory. If we want to allow for macro arguments, we need an extra macro for the check.

```
277   \@testopt\XTR@@extractline\@nil
278 }
```

`\XTR@@extractline` [*label*] *text* *eof*

The workhorse that reads input until the end of the line. Use the `\lowercase` trick for the definition.

```
279 \begingroup
280   \catcode'\~= \active\lccode'\~= '\^M
281 \lowercase{\endgroup
282   \def\XTR@@extractline[#1]#2~{%
```

Check state.

```
283   \ifXTR@active
284     \def\XTR@tempa{#1}%
285     \ifx\XTR@tempa\@nnil\else
286       \KV@@sp@def\XTR@currentlabel{#1}%
287     \fi
288     \XTR@checkxtr{extract}{line}%
289   \else
290     \XTR@extractfalse
291   \fi
292   \ifXTR@extract\XTR@writeout{#2}\fi
```

If we need to execute the line, the catcodes are wrong, so write it to the temporary file and insert it again when the catcodes are reset by `\endgroup`.

```
293     \ifXTR@st\XTR@opentmp\XTR@writetmp{#2}\XTR@closetmp\fi
294   \endgroup
```

Insert original content.

```
295   \ifXTR@st
296     \input{\jobname.xtr}%
297   \fi
298 }%
299 }
```

Only define the following macros when the package is active. This branch also performs redefinitions of the macros and environments that should be extracted.

```
300 \ifXTR@active
```

Start writing the target file.

```
301 \immediate\openout\XTR@out\XTR@file\relax
```

Write header to the target file.

```
302 \ifXTR@header
```

Compute the time.

```
303 \@tempcnta\time
304 \divide\@tempcnta 60
305 \edef\XTR@tempb{%
306   \the\year/\ifnum\the\month<10 0\fi\the\month/%
307   \ifnum\the\day<10 0\fi\the\day,\the\@tempcnta:%
308 }
309 \multiply\@tempcnta 60
310 \@tempcntb\time
311 \advance\@tempcntb-\@tempcnta
312 \ifnum\@tempcntb<10
313   \xdef\XTR@tempb{\XTR@tempb0\the\@tempcntb}
314 \else
315   \xdef\XTR@tempb{\XTR@tempb\the\@tempcntb}
316 \fi
317 \begingroup
```

Save the % character.

```
318 \catcode'\%=12
319 \gdef\XTR@tempa{%%\space}
320 \endgroup
```

Write all information to the target file.

```
321 \XTR@writeout{\XTR@tempa}
322 \filename@parse\XTR@file
323 \ifx\filename@ext\relax\def\filename@ext{tex}\fi
324 \XTR@writeout{%
325   \XTR@tempa This is file, '\filename@base.\filename@ext',%
326 }
327 \XTR@writeout{%
328   \XTR@tempa generated with the extract package.^^J\XTR@tempa
329 }
330 \XTR@writeout{\XTR@tempa Generated on : \space\XTR@tempb}
331 \filename@parse\jobname
332 \ifx\filename@ext\relax\def\filename@ext{tex}\fi
333 \XTR@writeout{%
334   \XTR@tempa From source \space: \space\filename@base.\filename@ext
335 }
336 \XTR@writeout{%
337   \XTR@tempa Using options: \space\curname opt@extract.sty\endcsname
338 }
339 \XTR@writeout{\XTR@tempa}
340 \fi
```

If requested, reconstruct the `\documentclass` command using information from `xkeyval`.

```
341 \ifXTR@copydocumentclass
342   \def\XTR@tempa#1.cls\@nil{\def\XTR@tempa{#1}}
343   \expandafter\XTR@tempa\XKV@documentclass\@nil
344   \ifx\XKV@classoptionslist\@empty
345     \XTR@writeout{\string\documentclass{\XTR@tempa}}
346   \else
347     \@temptokena\expandafter{\XKV@classoptionslist}%
348     \XTR@writeout{\string\documentclass[\the\@temptokena]{\XTR@tempa}}
349   \fi
```

```

350 \fi

Perform redefinitions at the beginning of the document.
351 \AtBeginDocument{%
352   \ifXTR@handles
353     \XTR@writeout{}%
354     \XTR@writeout{\string\begin{document}}%
355   \fi

Redefine environments.
356   \XKV@ifundefined{XTR@envs}{-}{%
357     \XKV@for@o\XTR@envs\XTR@tempa{%

Check whether the environment is defined.
358       \XKV@ifundefined\XTR@tempa{%
359         \XTR@err{%
360           environment ‘\XTR@tempa’ not defined; extraction canceled%
361         }%
362       }{%

Backup the beginning of the environment.
363       \XTR@namelet{XTR\XTR@tempa}\XTR@tempa}%

Redefine the beginning of the environment. This uses verbatim internally.
364       \@namedef{\XTR@tempa\expandafter}\expandafter{\expandafter
365         \def\expandafter\XTR@tempa\expandafter{\XTR@tempa}%

Check whether the current environment should be extracted. Note that \XTR@tempa
contains the current environment name.
366       \XTR@checkxtr{extract}\XTR@tempa
367       \ifXTR@extract

If extraction is required, write to the target file and to a temporary file for inclusion
afterwards.
368       \XTR@writeout{\XTR@opentmp
369         \@bsphack
370         \let\do\@makeother\dospecials\catcode‘\~M\active

\verbatim@processline Process macro for verbatim.
371       \def\verbatim@processline{%

\verbatim@processline is redefined here since the first line is treated specially, see
below.
372       \let\verbatim@processline\XTR@processline@begin

Write the content to the files.
373       \XTR@writeout{%
374         \string\begin{\XTR@tempa}\the\verbatim@line
375       }%
376       \XTR@writetmp{%
377         \string\begin{XTR\XTR@tempa}\the\verbatim@line
378       }%
379     }%

380     \XTR@sttrue\let\XTR@tempb\verbatim@
381     \else

```

Else, execute the backup of the current environment.

```
382     \edef\XTR@tempb{\noexpand\begin{XTR\XTR@tempa}}%
383     \fi
384     \XTR@tempb
385     }%
```

Backup the end of the environment.

```
386     \XTR@namelet{endXTR\XTR@tempa}{end\XTR@tempa}%
```

Redefine the end of the environment.

```
387     \@namedef{end\XTR@tempa\expandafter}\expandafter{\expandafter
388     \def\expandafter\XTR@tempa\expandafter{\XTR@tempa}%
389     \ifXTR@extract
390     \@esphack
```

Finalize writing and add the `\input` to the hook at the end of the current environment.

```
391     \XTR@writeout{\string\end{\XTR@tempa}}%
392     \XTR@writetmp{\string\end{XTR\XTR@tempa}}%
393     \XTR@closetmp
394     \AfterEndEnv{\input{\jobname.xtr}}%
395     \else
```

If not extracting, execute the backup of the end of the environment.

```
396     \edef\XTR@tempa{\noexpand\end{XTR\XTR@tempa}}%
397     \expandafter\XTR@tempa
398     \fi
399     }%
400     }%
401     }%
402     }%
```

Redefine commands using the arguments.

```
403 \XKV@ifundefined{XTR@cmdsargs}{}{%
```

Once backup the current definitions.

```
404 \let\XTR@sect\@sect
405 \let\XTR@chapter\@chapter
406 \def\XTR@tempb{chapter}%
```

Redefine a list of macros to write themselves to the target file. Chapters and section are treated differently since they are constructed differently. `\chapter*` will not extract itself since this gives technical difficulties due to the fact that this macro is reused at several places inside other macros, taking none-character input in its argument.

```
407 \XKV@for@o\XTR@cmdsargs\XTR@tempa{%
408 \XKV@ifundefined\XTR@tempa{%
409 \XTR@err{command '@backslashchar\XTR@tempa' not defined;
410 extraction canceled%
411 }%
412 }{%
```

Check whether allowed or not.

```
413 \@expandtwoargs\in@{,\XTR@tempa,}%
414 {,chapter,section,subsection,subsubsection,}%
415 \ifin@
416 \ifx\XTR@tempa\XTR@tempb
417 \def\@chapter[#1]#2{%
```

Check whether to extract this chapter or not.

```
418         \XTR@checkxtr{extract}{chapter}%
419         \ifXTR@extract
420         \XTR@writeout{}%
421         \def\XTR@tempa{#1}%
422         \def\XTR@tempb{#2}%
423         \ifx\XTR@tempa\XTR@tempb
424         \temptokena{#2}%
425         \else
426         \temptokena{[#1]{#2}}%
427         \fi
```

Write to file.

```
428         \XTR@writeout{\string\chapter\the\temptokena}%
429         \fi
```

Typeset the chapter.

```
430         \XTR@chapter[#1]{#2}%
431         }%
432         \else
```

We do a similar thing for sections created with \@sect.

```
433         \def\@sect#1#2#3#4#5#6[#7]#8{%
434         \@expandtwoargs\in@{,#1,}{,\XTR@cmdsargs,}%
435         \ifin@
436         \XTR@checkxtr{extract}{#1}%
437         \ifXTR@extract
438         \XTR@writeout{}%
439         \def\XTR@tempa{#7}%
440         \def\XTR@tempb{#8}%
441         \ifx\XTR@tempa\XTR@tempb
442         \temptokena{#8}%
443         \else
444         \temptokena{[#7]{#8}}%
445         \fi
446         \XTR@writeout{\expandafter
447         \string\csname#1\endcsname\the\temptokena}%
448         \fi
449         \fi
450         \XTR@sect{#1}{#2}{#3}{#4}{#5}{#6}[#7]{#8}%
451         }%
452         \fi
453         \else
454         \XTR@err{unsupported command ‘\XTR@tempa’;
455         try the ‘extract-cmdline option’}%
456         \fi
457         }%
458         }%
459         }%
460         \XKV@ifundefined{XTR@cmdslne}{}{%
```

Redefine a list of commands to write themselves and the text on the same line to the target file. This works similar to \extractline.

```
461         \XKV@for@o\XTR@cmdslne\XTR@tempa{%
462         \XKV@ifundefined\XTR@tempa{%
```



Check whether the command is defined.

```
463     \XTR@err{command ‘\@backslashchar\XTR@tempa’ not defined;
464     extraction canceled}%
465 }{%
```

Check whether allowed or not.

```
466     \@expandtwoargs\in@{,\XTR@tempa,}%
467     {,chapter,section,subsection,subsubsection,}%
468     \ifin@
469     \XTR@err{%
470     use the ‘extract-cmd’ option for command ‘\XTR@tempa’%
471     }%
472     \else
```

Backup the command.

```
473     \XTR@namelet{XTR\XTR@tempa}{\XTR@tempa}%
```

Redefine the command. Note that, inside the definition of the command, \XTR@tempa contains the command name.

```
474     \@namedef{\XTR@tempa\expandafter}\expandafter{\expandafter
475     \def\expandafter\XTR@tempa\expandafter{\XTR@tempa}%
```

Check whether this command should be extracted.

```
476     \XTR@checkxtr{extract}\XTR@tempa
477     \begingroup
478     \let\do\@makeother\dospecials\catcode‘\~M\active
479     \XTR@extractcmdline
480     }%
481     \fi
482     }%
483     }%
484     \begingroup
485     \catcode‘\~=\active\lccode‘\~='‘\~M
```

`\XTR@extractcmdline` *<text>**<eol>*

Workhorse for the command line extraction method. This macros reads until the next end of line and saves the content in \XTR@tempb.

```
486     \lowercase{\endgroup
487     \def\XTR@extractcmdline#1~{\verbatim@line{#1}\XTR@@extractcmdline}%
488     }%
```

`\XTR@@extractcmdline` Finalize the operation with the content of the current line. We write it to a target file and to a temporary file for execution in the current document. Note that \XTR@tempa still contains the current command name.

```
489     \def\XTR@@extractcmdline{%
490     \XTR@writeout{}%
491     \XTR@writeout{\expandafter\string\csname\XTR@tempa
492     \endcsname\the\verbatim@line
493     }%
494     \XTR@opentmp
495     \XTR@writetmp{\expandafter\string\csname XTR\XTR@tempa
496     \endcsname\the\verbatim@line
497     }%
498     \XTR@closetmp
499     \endgroup
```

```

500     \input{\jobname.xtr}%
501   }%
502 }%
503 }

```

Finalize writing the target file.

```

504 \AtEndDocument{%
505   \ifXTR@handles
506     \XTR@writeout{}%
507     \XTR@writeout{\string\end{document}}%
508   \fi
509   \immediate\closeout\XTR@out
510 }
511 \fi
512 </extract>

```

## References

- [1] Hendri Adriaens. xkeyval package. CTAN:/macros/latex/contrib/xkeyval.
- [2] Donald Arseneau. selectp package, v0.9. CTAN:/macros/latex/contrib/misc, 1992/09/25.
- [3] Donald Arseneau. optional package, v2.2. CTAN:/macros/latex/contrib/misc, 2001/09.
- [4] Stephen Bellantoni. version package. CTAN:/macros/latex/contrib/misc, 1990.
- [5] Johannes Braams, David Carlisle, Alan Jeffrey, Leslie Lamport, Frank Mittelbach, Chris Rowley, and Rainer Schöpf. The  $\text{\TeX}2_{\epsilon}$  sources. CTAN:/macros/latex/base, 2003.
- [6] Victor Eijkhout. comment package, v3.6. CTAN:/macros/latex/contrib/comment, 1999/10.
- [7] Carsten Heinz. listings package, v1.3. CTAN:/macros/latex/contrib/listings, 2004/09/07.
- [8] Uwe Lück. versions package, v0.51. CTAN:/macros/latex/contrib/versions, 2003/10/15.
- [9] Dan Luecking. excludeonly package, v1.0. CTAN:/macros/latex/contrib/misc, 2003/03/14.
- [10] Andreas Matthias. pdfpages package, v0.3e. CTAN:/macros/latex/contrib/pdfpages, 2004/01/31.
- [11] Heiko Oberdiek. pagesel package, v1.1. CTAN:/macros/latex/contrib/oberdiek, 1999/04/13.
- [12] Pablo A. Straub. askinclude package, v1.2e. CTAN:/macros/latex/contrib/misc, 1994/11/11.

- [13] Rainer Schöpf. `verbatim` package, v1.5q. CTAN:/macros/latex/required/tools, 2003/08/22.
- [14] Timothy Van Zandt. `xcomment` package, v1.2. CTAN:/macros/latex/contrib/seminar, 1993/02/12.
- [15] Timothy Van Zandt. `fancyvrb` package, v2.6. CTAN:/macros/latex/contrib/fancyvrb, 1998/07/17.

## Acknowledgements

Thanks go to David Carlisle for proposing the technique implemented in this package to solve my initial problem.<sup>7</sup> Thanks also go to Michael Kohlhase and Johannes Lubert for reporting bugs and providing ideas for extensions of the package.

## Version history

<b>v1.0</b>	<i>(2004/12/19)</i>
General: Initial release .....	1
<b>v1.1</b>	<i>(2005/01/01)</i>
General: Added conditional extraction using labels .....	1
Revised documentation .....	1
<code>\verbatim@processline</code> : Made to write content on same line as environment heading if so in source file .....	22
<b>v1.2</b>	<i>(2005/01/06)</i>
General: Fixed <code>\AfterEndEnv</code> hook for nested environments .....	1
Increased efficiency of the package .....	1
Simplified optional argument check for <code>extract</code> environment .....	1
<b>v1.3</b>	<i>(2005/01/12)</i>
General: Added <code>\extractline</code> .....	1
Added <code>document-handles</code> option .....	1
Added examples and documentation .....	1
Added line extraction method for commands .....	1
Removed some input checks for more flexibility .....	1
Simplified package .....	1
Updated license information .....	1
<code>\extractionlabel</code> : Was <code>\extractlabel</code> .....	16
<b>v1.4</b>	<i>(2005/02/06)</i>
General: Added <code>extractskip</code> environment .....	1
Adjusted options section for <code>xkeyval</code> ( <code>\XKV@tkey</code> not defined anymore) .....	1
Allow for any filename .....	1
Changed temp extension to <code>.xtr</code> .....	1
<code>\XTR@extractcmdline</code> : Changed temp macro to token register .....	25
<b>v1.5</b>	<i>(2005/02/08)</i>
General: Avoid using counters for conditional extraction with numbers .....	1
Solved bug in options section .....	1
<b>v1.6</b>	<i>(2005/02/14)</i>
General: Added optional header for extracted files .....	1
Improved options section .....	1
<b>v1.7</b>	<i>(2005/03/31)</i>

---

<sup>7</sup>See section 1.

General: Revised documentation .....	1
Solved small bug with 'no-header' option .....	1
<b>v1.8</b> .....	<i>(2005/05/07)</i>
General: Added copydocumentclass option .....	1
Changed name of option document-handles to handles .....	1
Changed name of option no-header to header .....	1
Revised documentation and examples .....	1
\XTR@processline@write: Solved bug of not copying empty lines to the target file ...	19
<b>v1.9a</b> .....	<i>(2019/09/18)</i>
\begin: Added definitions for robust versions of \begin and \end .....	13

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

<b>Symbols</b>	
\%	318
-labels (option)	5, 12
-nrs (option)	4, 12
\@chapter	405, 417
\@envdepth	68, 79, 80, 87, 88, 101, 102, 109, 110, 117
\@ifl@t@r	69
\@sect	404, 433
\{	191
\}	191
\^	173, 276, 280, 370, 478, 485
\~	280, 485
<b>A</b>	
active (option)	2, 12
\AfterEndEnv	<u>115</u> , 265, 394
<b>B</b>	
\begin	<u>69</u> , <u>92</u>
<b>C</b>	
copydocumentclass (option)	9, 12
<b>E</b>	
\end	<u>83</u> , <u>105</u>
\endextract	<u>259</u>
\endextract*	<u>259</u>
\endextractskip	<u>268</u>
environments:	
extract	6, 7
extract*	6, 7
extractskip	8
\ExecuteOptionsX	46
\extract	<u>169</u>
extract (environment)	6, 7
\extract*	<u>169</u>
extract* (environment)	6, 7
extract-cmd (option)	3, 12
extract-cmdline (option)	3, 12
extract-env (option)	2, 12
extract-labels (option)	8, 12
extract-nrs (option)	8, 12
\extractionlabel	5, <u>167</u>
\extractline	7, <u>270</u>
\extractline*	7
\extractskip	<u>268</u>
extractskip (environment)	8
extractskip-labels (option)	9, 12
extractskip-nrs (option)	9, 12
<b>F</b>	
\fmtversion	69
<b>G</b>	
generate (option)	2, 12
<b>H</b>	
handles (option)	9, 12
header (option)	9, 12
<b>I</b>	
\ifXTR@active	52, 177, 283, 300
\ifXTR@copydocumentclass	341
\ifXTR@extract	..... 11, 254, 292, 367, 389, 419, 437
\ifXTR@handles	352, 505
\ifXTR@header	302
\ifXTR@skip	10, 240
\ifXTR@st	9, 186, 251, 263, 293, 295
<b>L</b>	
line-labels (option)	8, 12

line-nrs (option) .....	8, 12	\XTR@closetmp ..	<u>48</u> , 61, 264, 293, 393, 498
<b>O</b>		\XTR@cmdsargs .....	26, 407, 434
options:		\XTR@cmdsline .....	30, 461
-labels .....	5, 12	\XTR@currentlabel .....	
-nrs .....	4, 12	.....	134, 135, 147, <u>167</u> , 180, 221, 286
active .....	2, 12	\XTR@endextract .....	259–261
copydocumentclass .....	9, 12	\XTR@envs .....	22, 357
extract-cmd .....	3, 12	\XTR@err .....	
extract-cmdline .....	3, 12	.....	<u>12</u> , 45, 55, 65, 359, 409, 454, 463, 469
extract-env .....	2, 12	\XTR@extract .....	169, 170, <u>171</u>
extract-labels .....	8, 12	\XTR@extractcmdline .....	479, <u>486</u>
extract-nrs .....	8, 12	\XTR@extractfalse .....	184, 290
extractskip-labels .....	9, 12	\XTR@extractline .....	271, 272, <u>274</u>
extractskip-nrs .....	9, 12	\XTR@file .....	20, 63, 301, 322
generate .....	2, 12	\XTR@maketrue .....	123, 137, 154, 158, 160, 163
handles .....	9, 12	\XTR@namelet .....	<u>13</u> , 36, 121, 269, 363, 386, 473
header .....	9, 12	\XTR@opentmp .....	<u>48</u> , 57, 186, 293, 368, 494
line-labels .....	8, 12	\XTR@orig@line .....	195, 197, 234, 236, 257
line-nrs .....	8, 12	\XTR@out .....	7, 51, 301, 509
<b>V</b>		\XTR@processline@begin .....	
\verbatim@ .....	380	.....	187, <u>193</u> , 243, 372
\verbatim@line .....	195, 196, 201, 234, 235,	\XTR@processline@end .....	206, <u>232</u>
240, 254, 255, 374, 377, 487, 492, 496		\XTR@processline@write .....	203, 242, <u>250</u>
\verbatim@processline .....	187, 206, 243, <u>371</u>	\XTR@sect .....	404, 450
\verbatim@start .....	188	\XTR@sk@plabel .....	222, <u>228</u>
<b>X</b>		\XTR@skiplabel .....	204, <u>214</u>
\XTR@@xtract .....	174, <u>176</u>	\XTR@t@stbegin .....	208, 210, <u>229</u>
\XTR@@xtractcmdline .....	487, <u>489</u>	\XTR@t@stend .....	244, <u>247</u>
\XTR@@xtractline .....	277, <u>279</u>	\XTR@testbegin .....	197, <u>199</u> , 248
\XTR@ch@ck@tr .....	150, <u>152</u>	\XTR@testend .....	230, 236, <u>238</u>
\XTR@ch@ckxtr .....	143, <u>149</u>	\XTR@tmp .....	8, 48–50
\XTR@chapter .....	405, 430	\XTR@writeout .....	<u>48</u> , 255, 257, 292,
\XTR@checkxtr .....		.....	321, 324, 327, 330, 333, 336, 339,
.....		.....	345, 348, 353, 354, 368, 373, 391,
<u>119</u> , 182, 205, 288, 366, 418, 436, 476		\XTR@writetmp .....	420, 428, 438, 446, 490, 491, 506, 507
		.....	
		.....	<u>48</u> , 58, 252, 257, 293, 376, 392, 495